

# transitional

## slim flush mount ceiling fixture



### Features

- Light Appearance: 3000K
- CRI 80+
- Ultra Slim, Low Profile
- TRIAC Dimmable
- Mounting Accessories Included with Optional O-Ring for Wet Applications
- Lifetime 35,000 Hours
- Retrofit Kit (RK) Includes E26 Socket Adapter

### Available Finishes

- **White (WT)**  
with Frosted Lens
- **Brushed Nickel (BN)**  
with Frosted Lens



Finish	Dimensions	Watts	Delivered Lumens	Retrofit Kit Included	Energy Star	Model No.	Product ID No.
●	5.5" x 1.25"	12w	840	-		B335MS12W30WT	.3388912
	5.5" x 1.25"	12w	840	✓		B335MS12W30WTRK	.3405123
	7.7" x 1.25"	15w	950	-		B338MS15W30WT	.3388647
	7.7" x 1.25"	15w	950	✓		B338MS15W30WTRK	.3405133
	12" x 1.25"	17w	1100	-		B3312MS17W30WT	.3388650
●	5.5" x 1.25"	12w	840	-		B335MS12W30BN	.3388911
	5.5" x 1.25"	12w	840	✓		B335MS12W30BNRK	.3405131
	7.7" x 1.25"	15w	950	-		B338MS15W30BN	.3388645
	7.7" x 1.25"	15w	950	✓		B338MS15W30BNRK	.3405135
	12" x 1.25"	17w	1100	-		B3312MS17W30BN	.3388651